

Amendments to the Claims:

Status of Claims:

Claims 1-19, 21 and 23-37 are pending.

Claim 13 is canceled by the present amendment.

Claims 1, 14, 23, 25, 28, 35 are in independent form.

1. (Previously Presented) A system for a storage device, comprising:
an access controller configured to control access requests to a storage device by metering access to data within a first predefined region within the storage device and by allowing unmetered access to data within a second predefined region within the storage device.
2. (Original) The system of claim 1, where the system is embedded in one of, a database system, an operating system, and an application configured to process access requests to the storage device.
3. (Original) The system of claim 1, where the system further includes allocation logic configured to determine a priority for data to be written to the storage device and causing the data to be stored within the first region or the second region based on the priority.
4. (Original) The system of claim 3 where the priority of the data includes a plurality of priority levels.
5. (Original) The system of claim 1 where the storage device includes one or more disk drives.

6. (Original) The system of claim 1 where the storage device includes a disk and where the second region is defined closer to a perimeter of the disk than the first region.
7. (Original) The system of claim 6 where the first region and the second are defined by one or more logical block addresses.
8. (Original) The system of claim 1, where the system is embedded in a file system configured to process data input and output requests to the storage device.
9. (Original) The system of claim 1 where the access requests include at least one of data input and data output requests.
10. (Original) The system of claim 1, where the access controller is configured to meter access based on a threshold of access requests directed to the data within the first region.
11. (Original) The system of claim 1 further including one or more tables configured to define at least the data in the first region to be metered.
12. (Original) The system of claim 11 where the data in the one or more tables is configured to define one or more of, a file, an application, and a data location.
13. (Canceled)
14. (Currently Amended) A [[The]] method, comprising: of claim 13
receiving access requests to a storage device; and

increasing response time for access requests to a first predefined region within the storage device by metering access requests to a second predefined region within the storage device;

where the metering includes limiting a number of access requests to the second region based on a threshold number of the access requests.

15. (Currently Amended) The method of claim 14 ~~[[13]]~~ further including storing data to be metered within the storage device based on a priority level of the data.
16. (Currently Amended) The method of claim 14 ~~[[13]]~~ further including determining, for a selected data, whether the selected data will be stored within the first region or the second region.
17. (Currently Amended) The method of claim 14 ~~[[13]]~~ further including:
defining a plurality of regions within the storage device; and
assigning a metering threshold for selected regions of the plurality of regions.
18. (Original) The method of claim 17 where the plurality of regions are defined by setting one or more addresses within the storage device.
19. (Currently Amended) The method of claim 14 ~~[[13]]~~ further including:
monitoring a number of access requests to the second region; and
initiating the metering when the number of access requests reaches a threshold.
20. (Canceled)

21. (Previously Presented) The method as set forth in claim 23 where the limiting includes restricting the I/O requests having the second priority level based on a threshold number of I/O requests having the second priority level.

22. (Canceled).

23. (Previously Presented) A method comprising:
receiving I/O requests directed to a storage device;
determining a priority level of each of the I/O requests;
allowing I/O requests having a first priority level to be processed;
limiting I/O requests having a second priority level,
where the priority level of an I/O request is determined based on a predefined location of data within the storage device associated with the I/O request; and
where data located adjacent a perimeter of the storage device receives the first priority level and where data located adjacent a hub of the storage device receives the second priority level.

24. (Previously Presented) The method as set forth in claim 23 where the location of the data is determined based on one or more predetermined addresses within the storage device.

24. (Currently Amended) The method as set forth in claim 23 20 where the location of the data is determined based on one or more predetermined addresses within the storage device.

25. (Previously Presented) A computer-readable medium storing processor executable instructions operable to perform a method, the method comprising:

processing access requests to a storage device; and

controlling the access requests to the storage device by metering access to data within a first predefined region within the storage device and by allowing unmetered access to data within a second predefined region within the storage device.

26. (Original) The computer-readable medium as set forth in claim 25 where the storage device includes a disk drive.

27. (Original) The computer-readable medium as set forth in claim 25 further including processor executable instructions operable to cause a processor to store data to the storage device based on a priority of the data, the data being stored in one of the first region and the second region.

28. (Previously Presented) A computer-readable medium storing processor executable instructions operable to perform a method, the method comprising:

processing access requests to a storage device;

metering access requests to a first predefined region within the storage device to maintain response time for access requests to a second predefined region within the storage device; and

setting a threshold value of access requests, where access requests to the first region are caused to be metered after the threshold value of access requests are processed.

29. (Original) The computer-readable medium as set forth in claim 25 where the metering includes limiting a number of the access requests to the first region from being processed.

30. (Previously Presented) The computer-readable medium as set forth in claim 25 where the processing includes determining to which region each of the access requests is directed.

31. (Original) The computer-readable medium as set forth in claim 25 further including processor executable instructions operable to cause a processor to define at least the first region and the second region within the storage device.

32. (Original) The computer-readable medium as set forth in claim 25 including means for allocating data to a selected region within the storage device.

33. (Original) The computer-readable medium as set forth in claim 25 where the computer-readable medium is integrated with at least one of: a data base system, a file system, an operating system, and the storage device.

34. (Original) The computer-readable medium as set forth in claim 25 further including access controller means for metering access requests to the first region.

35. (Previously Presented) A database system configured to process access requests to a storage device, the system comprising:
allocation logic configured to define a plurality of regions within the storage device based on information received from a user;
threshold logic configured to assign a metering threshold to one or more selected regions of the plurality of regions; and
an access controller configured to process access requests to the storage device, the access controller including logic configured to meter access requests to a selected region of the plurality of regions once a metering threshold for the selected region is met.

36. (Original) The database system of claim 35 where the allocation logic is further configured to cause selected data to be placed within a selected region of the plurality of regions based on a frequency of access to the selected data.

37. (Original) The database system of claim 35 where the access controller includes means for metering access requests.